

INCH-POUND

MIL-DTL-83296A
SUPPLEMENT 1
29 September 2000

DETAIL SPECIFICATION

FITTINGS, CORROSION RESISTANT STEEL, HIGH TEMPERATURE
HIGH PRESSURE (3000 PSI), HYDRAULIC AND PNEUMATIC

This supplement forms a part of MIL-DTL-83296, dated 29 September 2000.

| | |
|---------|--|
| MS27616 | Adapter Assembly, Flared, Straight, Tube to Hose - with Swivel Nut |
| MS27617 | Adapter Assembly, Flared, 45° Elbow, Tube to Hose - with Swivel Nut |
| MS27618 | Adapter, Assembly, Flared, 90° Elbow, Tube to Hose - with Swivel Nut |
| MS27619 | Nipple, Sub Assembly, Flared, Straight - with Swivel Nut |
| MS27620 | Elbow Sub Assembly, Flared, 45°, Swivel Nut |
| MS27621 | Elbow Sub Assembly, Flared, 90°, Swivel Nut |
| MS27622 | Socket, Hose Coupling |
| MS27623 | Sleeve, Hose Coupling |
| MS27624 | Union, Nipple |
| MS27625 | Wire, Retainer |
| MS27626 | Nipple, Flared, Tube to Hose - Swivel Nut |
| MS27627 | Elbow, Flared, Tube to Hose - 90°, Swivel Nut |
| MS27628 | Elbow, Flared, Tube to Hose - 45°, Swivel Nut |
| MS27629 | Adapter Assembly, Flareless, Straight, Tube to Hose - with Swivel Nut |
| MS27630 | Adapter Assembly, Flareless, 45° Elbow, Tube to Hose - with Swivel Nut |
| MS27631 | Adapter Assembly, Flareless, 90° Elbow, Tube to Hose - with Swivel Nut |
| MS27632 | Nipple Sub Assembly, Flareless, Straight-with Swivel Nut |
| MS27633 | Elbow Sub Assembly, Flareless, 45°, Swivel Nut |
| MS27634 | Elbow Sub Assembly, Flareless, 90°, Swivel Nut |
| MS27635 | Nipple, Flareless, Tube to Hose-Swivel Nut |
| MS27636 | Elbow, Flareless, Tube to Hose - 90°, Swivel Nut |
| MS27637 | Elbow, Flareless, Tube to Hose - 45°, Swivel Nut |
| MS27638 | Mandrel Sleeve Setting |
| MS27639 | Disassembly Tool |

Custodians:
Air Force - 99
Army - AV
Navy - AS
DLA - CCPreparing activity:
DLA - CC

(Project 4730-1040-001)

Review activities:
Air Force - 82
Navy - MC, SA

AMSC N/A

FSC 4730

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.