

INCH-POUND

MIL-C-44262A

5 January 1989

SUPERSEDING

MIL-C-44262

22 December 1986

MILITARY SPECIFICATION

CARROTS, SLICED, THERMOSTABILIZED, TRAY PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers sliced carrots thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.1).

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 8915

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

MIL-C-44262 A

MILITARY

- MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
- MIL-L-35078 - Loads, Unit; Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification for
- MIL-C-44340 - Can, Tray Pack

STANDARDS

MILITARY

- MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
- MIL-STD-129 - Marking for Shipment and Storage

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

U.S. DEPARTMENT OF AGRICULTURE (USDA)

- U.S. Standards for Grades of Canned Carrots
- U.S. Standards for Grades of Frozen Carrots

(Copies are available from the Director, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2077, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

United States Standards for Condition of Food Containers

(Copies are available from the Chairman, Condition of Food Container Committee, Agricultural Marketing Service, U.S. Department of Agriculture, Room 0608, South Building, P.O. Box 0608, Washington, DC 20090-6456.)

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR parts 1-199)

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

MIL-C-44262A

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies are available from the Office of Drinking Water Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.1).

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3330 - Peel Adhesion of Pressure-sensitive Tape

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, Washington, DC 20418.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

MIL-C-44262A

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.1), a sample shall be subjected to first article inspection (see 6.2) in accordance with 4.4.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Carrots, fresh. Carrots shall be fresh, firm, of good color and of a variety suitable for canning. The diameter of each carrot shall not be less than 0.75 inch nor more than 1.50 inches.

3.2.2 Carrots, sliced, frozen. The carrot slices shall be U.S. Grade A in accordance with U.S. Standards for Grades of Frozen Carrots and shall be of the latest season's crop. The carrot slices shall be 0.25 to 0.50 inches in thickness and have a diameter in the range of 0.75 to 1.50 inches.

3.2.3 Salt. Salt shall be non-iodized, white, refined sodium chloride, with or without anticaking agents, and shall comply with purity standards for sodium chloride of the Food Chemicals Codex.

3.2.4 Water. Water used for formulation, blanching, and washing shall conform to the National Primary Drinking Water Regulations.

3.3 Preparation and processing.

3.3.1 Carrot preparation.

3.3.1.1 Fresh carrot preparation. The carrots shall be washed thoroughly to remove soil and foreign material, and sorted to remove any that are diseased or otherwise damaged. The sound stock shall be peeled and trimmed to remove discolored or undesirable portions. The peeled carrots shall be sliced transversely to the longitudinal axis into 0.25 to 0.50 inch thick slices. The sliced carrots shall be blanched sufficiently to prevent discoloration and to remove excess air. The blanched carrots shall be immediately cooled and thoroughly drained. The cooled drained carrots shall be handled in a manner to prevent discoloration and shall be filled into the tray pack cans within 4 hours after blanching.

3.3.1.2 Frozen carrot preparation. Frozen carrots shall be thawed only to the extent necessary to accommodate the filling operation. The thawed carrot slices shall be handled in a manner to prevent discoloration.

MIL-C-44262A

3.3.2 Preparation of brine. Brine shall be prepared in a manner so as to assure compliance with finished product salt requirements. Brine shall be prepared fresh daily. Brine remaining at the end of a production day shall be discarded. Brine may be filled hot or cold.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with product so as to conform to the finished product requirements and to the following requirements:

- a. Each can shall be hermetically sealed under a vacuum established by a processing authority and specified in the scheduled process so as to assure compliance with the finished product requirement 3.6k.
- b. The filled and sealed tray pack can shall be in the retort process within 2 hours after sealing.

3.5 Tray pack thermoprocessing. The filled and sealed cans shall be thermostabilized by retorting until a sterilization value (F_0) of not less than 4.2 has been achieved. The filled and sealed thermoprocessed tray pack cans shall show no evidence of can swelling when tested for commercial sterility as specified in 4.5.3.4.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

- a. There shall be no foreign material such as, but not limited to, dirt, insects, insect parts, hair, wood, paper, paint, glass, or metal.
- b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, musty, moldy.
- c. There shall be no color foreign to the product.
- d. The product shall meet the requirements for U.S. Grade A, Sliced, Canned Carrots of the U.S. Standards for Grades of Canned Carrots except for size and texture. No slice shall be greater than 1-1/2 inches in diameter. Texture shall be U.S. Grade C or better of the U.S. Standards for Grades of Canned Carrots.
- e. No individual can shall have a net weight of less than 100 ounces.
- f. The average net weight shall be not less than 102 ounces.
- g. No individual can shall contain less than 66.0 ounces drained weight of sliced carrots.
- h. The average drained weight shall be not less than 69.0 ounces.

MIL-C-44262A

1. The salt content of the finished product shall be not greater than 1.3 percent nor less than 0.5 percent.
- j. The product shall show no evidence of excessive heating (materially darkened or scorched).
- k. Filled, sealed and retorted cans shall show evidence of proper vacuum as determined by concavity of the can lid (see 4.5.6).

3.6.1 Palatability. The product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110, Current Good Manufacturing Practice in Manufacturing, Processing, Packaging or Holding of Human Foods, and the plant sanitation requirements of the appropriate Government inspection agency.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act, and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection necessary to assure compliance with the requirements of this specification.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

- a. First article inspection (see 4.4).
- b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

MIL-C-44262A

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, and compliance be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods, such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.5.3.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 102 ounces or if the net weight of any individual can is less than 100 ounces, the lot shall be rejected.

4.5.3.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table I. The tray pack cans shall be selected at random from the lot. The tray pack cans shall be opened and inspected for the defects listed in table II.

MIL-C-44262A

TABLE I. Double sampling plan for product inspection. 1/

Lot size (cans)	Sample size (cans)	Cumulative sample	Acceptance number	Rejection number
0 to 3200	8	--	0	2
	8	16	1	2
3201 to 35000	13	--	0	3
	13	26	3	4

- 1/ a. If no defects are found in the first sample, the lot shall be accepted.
- b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.
- c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

TABLE II. Product defects 1/ 2/ 3/

Category	Defect
<u>Major</u>	
101	Drained weight of carrots in a can is less than 66.0 ounces <u>4/5/</u>
102	Product shows evidence of excessive heating (materially darkened or scorched)

- 1/ The presence of foreign material (for example, glass, dirt, insects, insect parts, hair, paper, paint, wood, metal), foreign odor or flavor (for example, burnt, scorched, moldy, musty, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.
- 2/ Product not meeting grade type and size, shall be cause for rejection of the lot.

MIL-C-44262A

- 3/ Product not equal to or better than the approved preproduction sample (see 6.1) in palatability or overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an Agricultural Marketing Service (AMS) agent.)
- 4/ To determine drained weight, the contents of the tray pack can shall be poured into a U.S. Standard No. 8 sieve in a manner that will distribute the product over the sieve without breaking the carrot slices. Sieve area shall be such that the distributed product does not completely cover all openings of the sieve. The sieve shall be tilted to approximately a 45 degree angle and allowed to drain for 2 minutes before determining the drained weight by subtracting the sieve tare weight from the gross weight. The drained weight shall be reported to the nearest 0.1 ounce.
- 5/ The lot shall be rejected if the sample average drained weight is less than 69.0 ounces.

4.5.3.3 Salt content testing. Nine tray packs shall be selected at random from the lot and distributed as follows:

- Three for laboratory analysis
- Three for submission to the contractor
- Three for retention by the AMS agent as reserve samples.

The three tray packs for laboratory analysis shall be individually tested for salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists. Preparation of the samples shall be as follows. The three cans shall be opened and thoroughly drained of all brine. Each can of drained carrots shall be separately blended in a Warning blender or equivalent. The test results shall be reported to the nearest 0.1 percent. Any test failure shall be classified as a major defect. The lot shall be rejected if the salt content of any individual tray pack is less than 0.5 percent or greater than 1.3 percent. Analysis of reserve samples at the request of the contractor shall not be permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of noncompliance with the salt content requirement. When the reserve samples are analyzed, the analysis for salt shall be made and will be considered final. Unused reserve samples shall be returned to the contractor for inclusion in subsequent lots.

4.5.3.4 Commercial sterility testing. The sample size shall be one filled, sealed, and thermoprocessed tray pack can selected from each retort batch in the lot. The sample cans shall be tested for sterility by incubating the cans at $95 \pm 5^\circ\text{F}$ for 10 days. Any evidence of can swelling shall be considered a critical defect and shall be cause for rejection of the lot.

MIL-C-44262A

4.5.4 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers except that inspection for labeling shall be in accordance with 4.5.4.1. In addition, the following defect shall be classified as a critical defect and shall be cause for rejection of the lot:

Evidence of buffing causing scratches or scuffing of exterior can coating.

4.5.4.1 Can label examination. Labels shall be examined for defects in accordance with MIL-L-1497 (see 5.4), except for self-adhering labels the following additional defects shall apply:

Major: Label torn or scratched so as to obliterate any of the markings.

Minor: Air bubbles under label.

Label not properly adhered to can, for example, label raised or peeled back from edges or corners.

4.5.4.2 Label adhesive examination. When self-adhering labels are used, the adhesive shall be tested in accordance with ASTM D 3330.

4.5.5 Can closure examination. Can closure shall be examined visually and by teardowns in accordance with CFR 21, Part 113, Subpart D or CFR 9, Part 318, Subpart G, as applicable. Any nonconformance based on observation of can seam teardowns or on record of can seam teardowns shall be classified as a major defect and shall be cause for rejection of any involved product.

4.5.6 Vacuum examination. Cans shall be allowed to cool to $75^{\circ} \pm 5^{\circ}\text{F}$, held for at least 24 hours after sealing, and then examined for vacuum retention. To examine, lay a straight edge in the center of the lid along the length of the tray pack. Both ends of the straight edge shall touch the lid at the inside edge of the double seam. There shall be a visible gap between the straight edge and the lid for the entire distance of the label panel. Using a shorter straight edge, the same procedure shall be used across the width, in the center of the tray pack can. One measurement shall be made when examining a ribbed lid; lay the straight edge between the two center ribs along the length of the can. The inspection lot shall include only tray packs produced in a single shift on a single sealing machine. The sample size shall be 50 cans. Any nonconformance shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.7 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

MIL-C-44262A

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
 Reinforced with other than nonmetallic strapping or tape.
 Dimensions of pads not as specified.
 Interior packing with fiberboard liner or pads not as specified.

Minor: Other required markings missing, incorrect, or illegible.
 Arrangement or number of cans not as specified.

4.5.8 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A.

5.1.1 Level A. One hundred two ounces of food product shall be filled into a tray pack can conforming to MIL-C-44340 and sealed and thermoprocessed as specified in 3.4 and 3.5. Buffing of the can causing damage to the exterior can coating is not permitted (see 4.5.4).

5.2 Packing. The product shall be packed in accordance with level A, B, or C as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L or HSC-L with an HSC full depth cover, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade V3c fiberboard. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box. Each box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1), except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1 except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

MIL-C-44262A

5.2.3 Level C packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 or 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.4 Labeling. Each package shall be labeled in accordance with MIL-L-1497 and with the following:

- Official establishment number (e.g., est 38) or a three letter code identifying the establishment.
- Lot number 1/
- Production shift number 1/
- Retort identification number 1/
- Retort cook number 1/

1/ The lot number shall be expressed as a four digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (Example, March 19, 1987, would be coded as 7078). The Julian code shall represent the day the product was packaged and processed. Sub-lotting (when used) shall be represented by an alpha character immediately following the four digit Julian code. Following the four-digit Julian code and the alpha character (when used), the other required code information shall be printed in the sequence as listed above.

In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined as specified in 4.5.4 after preparation of product in accordance with heating instructions. Paper labels are not permitted. Cans shall show the following statements:

MIL-C-44262A

TO HEAT IN WATER: Submerge unopened can in boiling water. Simmer gently for 15 - 20 minutes. Avoid overheating (can shows evidence of bulging).

CAUTION: Use care when opening as pressure may have been generated within the can.

TO HEAT IN OVEN: Either punch several holes in lid of can or open can in usual manner leaving the loose lid in place. Place in a 350°F oven for 35 - 40 minutes.

WARNING: Do not place unopened can in oven. This may cause the can to burst.

YIELD: For Army Field Feeding, serves 18 portions of 3/4 cup each.
For other uses, serves 25 portions of 1/2 cup each.

As an alternate labeling method, a preprinted, self-adhering, 0.002-inch thick, clear polyester label printed with indelible black ink may be used. Self-adhering labels shall be applied after retorting. Pressure-sensitive adhesive shall require no preparation prior to application. Labels shall tack quickly and adhere without curling or breaking. The adhesive shall have a minimum adhesion of 60 ounces per inch width when examined as specified in 4.5.4.2. When self-adhering label is used, the tray pack can shall be labeled with the Julian code and a product code prior to retorting.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary markings in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE,
UNLESS PALLET RACKS ARE USED

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

MIL-C-44262A

6.1 Acquisition requirements. Acquisition documents should specify the following:

- a. Title, number and date of this specification.
- b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
- c. When a first article is required (see 3.1, 4.4, and 6.2).
- d. Provisions for approved preproduction samples (see 3.6.1 and 6.2).
- e. Level of packing required (see 5.2).
- f. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.3 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.4 Subject term (key word) listing.

Canned food
 Combat field feeding
 Food processing
 Operational rations
 Shelf stable

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
 Navy - SA
 Air Force - 50

Preparing activity:

Army-GL
 (Project 8915-0835)

Review activities:

Army - MD, TS
 Navy - MC
 DP - SS

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL*(See Instructions - Reverse Side)*

1. DOCUMENT NUMBER MIL-C-44262A		2. DOCUMENT TITLE Carrots, Sliced, Thermostabilized, Tray Pack	
3a. NAME OF SUBMITTING ORGANIZATION		4. TYPE OF ORGANIZATION (Mark one)	
3b. ADDRESS (Street, City, State, ZIP Code)		<input type="checkbox"/> VENDOR	
		<input type="checkbox"/> USER	
		<input type="checkbox"/> MANUFACTURER	
		<input type="checkbox"/> OTHER (Specify): _____	
5. PROBLEM AREAS			
a. Paragraph Number and Wording:			
b. Recommended Wording:			
c. Reason/Rationale for Recommendation:			
6. REMARKS			
7a. NAME OF SUBMITTER (Last, First, MI) - Optional		b. WORK TELEPHONE NUMBER (Include Area Code) - Optional	
c. MAILING ADDRESS (Street, City, State, ZIP Code) - Optional		8. DATE OF SUBMISSION (YYMMDD)	

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge (**DO NOT STAPLE**), and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 12662 WASHINGTON, D.C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

