



REVIEWER: GL, IS, ME, MI
USER: AT, AV

DASH NUMBER	SIZE	OUTSIDE DIMENSIONS (APPROX)	WEIGHT PER DOZEN (APPROX LBS)	(A) BREAKING LOAD MIN
(A) 21	3/16	1-1/4 x 3/4	3/8	2600
1	1/4	1-1/2 x 1	3/4	4500
2	5/16	1-11/16 x 1-3/16	1	6800
3	3/8	2-1/16 x 1-3/8	2	9300
4	7/16	2-3/8 x 1-1/2	3-1/8	12500
5	1/2	2-5/8 x 1-3/4	4-1/2	16500
6	9/16	3 x 1-15/16	6-5/8	20500
7	5/8	3-5/16 x 2-3/16	9	25000
(A) 8	11/16	3-1/2 x 2-5/16	11	29300
9	3/4	3-7/8 x 2-1/2	14-1/2	35400
10	7/8	4-1/2 x 2-15/16	20-1/4	48000
11	1	5 x 3-1/4	29	62000
12	1-1/8	5-5/8 x 3-1/2	40	78000
(A) 22	1-1/4	6-1/8 x 4	53-1/2	96000

(A) *CANCELLED IN PART after 5 December 1975. No other superseding standard. See RR-C-271 for superseding links.

NOTES:

- (A) 1. **MATERIAL:** Forged carbon steel in accordance with Grade C of RR-C-271.
- (A) 2. **PROTECTIVE COATING:** Zinc coating, hot-dip galvanized, in accordance with ASTM A153 or electro deposited in accordance with QQ-Z-325, type II, class 3.
3. **DIMENSIONS:** All dimensions are in inches unless otherwise specified.
4. **PART NUMBER:** The MS part number consists of the MS number plus the dash number.
Example: MS87008-1.
5. Referenced documents shall be of the issue in effect on date of invitations for bid.
6. For design feature purposes this standard takes precedence over procurement documents referenced herein.

This secondary standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A.	4C	TITLE	MILITARY STANDARD
Other Cast	2 SH	LINK, CHAIN- CONNECTING OR REPAIR	MS87008
PROCUREMENT SPECIFICATION	RR-C-271	SUPERSEDES:	SHEET 1 OF 1
		SDX1	